

# CCNA Exploration 4.0: ESwitching Basic Switching / Wireless PT Practice SBA

## Switch S1

```
S1#sh ru
Building configuration...

Current configuration : 1639 bytes
!
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname S1
!
enable secret 5 $1$mERr$9cTjUIEqNGurQiFU.ZeCi1
!
!
!
!
spanning-tree mode pvst
spanning-tree vlan 1-80 priority 12288
!
interface FastEthernet0/1
!
interface FastEthernet0/2
!
interface FastEthernet0/3
!
interface FastEthernet0/4
!
interface FastEthernet0/5
!
interface FastEthernet0/6
!
interface FastEthernet0/7
!
interface FastEthernet0/8
!
interface FastEthernet0/9
!
interface FastEthernet0/10
!
interface FastEthernet0/11
!
interface FastEthernet0/12
!
interface FastEthernet0/13
!
interface FastEthernet0/14
!
interface FastEthernet0/15
!
interface FastEthernet0/16
!
interface FastEthernet0/17
!
interface FastEthernet0/18
!
```

```
interface FastEthernet0/19
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/20
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/21
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/22
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/23
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/24
  switchport trunk native vlan 55
  switchport mode trunk
!
interface GigabitEthernet1/1
!
interface GigabitEthernet1/2
!
interface Vlan1
  no ip address
  shutdown
!
interface Vlan55
  ip address 10.10.55.11 255.255.255.0
!
ip default-gateway 10.10.55.1
!
banner motd ^CAuthorized Access Only!^C
!
line con 0
  password cisco
  login
!
line vty 0 4
  password cisco
  login
line vty 5 15
  password cisco
  login
!
!
end

S1#
```

# Switch S2

```
S2#
S2#sh ru
Building configuration...

Current configuration : 2506 bytes
!
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname S2
!
enable secret 5 $1$mERr$9cTjUIEqNGurQiFU.ZeCi1
!
!
!
spanning-tree mode pvst
spanning-tree vlan 1-80 priority 16384
!
interface FastEthernet0/1
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/2
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/3
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/4
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/5
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/6
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/7
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/8
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/9
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/10
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/11
  switchport access vlan 50
```

```
switchport mode access
!
interface FastEthernet0/12
switchport access vlan 50
switchport mode access
!
interface FastEthernet0/13
switchport access vlan 50
switchport mode access
!
interface FastEthernet0/14
switchport access vlan 50
switchport mode access
!
interface FastEthernet0/15
switchport access vlan 50
switchport mode access
!
interface FastEthernet0/16
switchport access vlan 50
switchport mode access
!
interface FastEthernet0/17
switchport access vlan 50
switchport mode access
!
interface FastEthernet0/18
!
interface FastEthernet0/19
switchport trunk native vlan 55
switchport mode trunk
!
interface FastEthernet0/20
switchport trunk native vlan 55
switchport mode trunk
!
interface FastEthernet0/21
switchport trunk native vlan 55
switchport mode trunk
!
interface FastEthernet0/22
switchport trunk native vlan 55
switchport mode trunk
!
interface FastEthernet0/23
switchport trunk native vlan 55
switchport mode trunk
!
interface FastEthernet0/24
switchport trunk native vlan 55
switchport mode trunk
!
interface GigabitEthernet1/1
!
interface GigabitEthernet1/2
!
interface Vlan1
no ip address
shutdown
!
interface Vlan55
ip address 10.10.55.12 255.255.255.0
!
ip default-gateway 10.10.55.1
!
banner motd ^CAuthorized Access Only!^C
```

```
!  
line con 0  
  password cisco  
  login  
!  
line vty 0 4  
  password cisco  
  login  
line vty 5 15  
  password cisco  
  login  
!  
!  
end
```

S2#

# Switch S3

```
S3#sh ru
Building configuration...

Current configuration : 2686 bytes
!
version 12.2
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname S3
!
enable secret 5 $1$mERr$9cTjUIEqNGurQiFU.ZeCi1
!
!
!
spanning-tree mode pvst
!
interface FastEthernet0/1
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/2
  switchport access vlan 40
  switchport mode access
  switchport port-security
  switchport port-security maximum 2
  switchport port-security mac-address sticky
  switchport port-security mac-address sticky 0050.0FDE.754B
!
interface FastEthernet0/3
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/4
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/5
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/6
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/7
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/8
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/9
  switchport access vlan 40
  switchport mode access
!
interface FastEthernet0/10
  switchport access vlan 40
  switchport mode access
!
```

```
interface FastEthernet0/11
  switchport access vlan 50
  switchport mode access
!
interface FastEthernet0/12
  switchport access vlan 50
  switchport mode access
!
interface FastEthernet0/13
  switchport access vlan 50
  switchport mode access
!
interface FastEthernet0/14
  switchport access vlan 50
  switchport mode access
!
interface FastEthernet0/15
  switchport access vlan 50
  switchport mode access
!
interface FastEthernet0/16
  switchport access vlan 50
  switchport mode access
!
interface FastEthernet0/17
  switchport access vlan 50
  switchport mode access
!
interface FastEthernet0/18
  switchport access vlan 80
  switchport mode access
!
interface FastEthernet0/19
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/20
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/21
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/22
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/23
  switchport trunk native vlan 55
  switchport mode trunk
!
interface FastEthernet0/24
  switchport trunk native vlan 55
  switchport mode trunk
!
interface GigabitEthernet1/1
!
interface GigabitEthernet1/2
!
interface Vlan1
  no ip address
  shutdown
!
interface Vlan55
  ip address 10.10.55.13 255.255.255.0
```

```
!  
ip default-gateway 10.10.55.1  
!  
banner motd ^CAuthorized Access Only!^C  
!  
line con 0  
  password cisco  
  login  
!  
line vty 0 4  
  password cisco  
  login  
line vty 5 15  
  password cisco  
  login  
!  
!  
end
```

S3#



# Router BRANCH

```
Branch#sh ru
Building configuration...

Current configuration : 1034 bytes
!
version 12.4
no service timestamps log datetime msec
no service timestamps debug datetime msec
no service password-encryption
!
hostname Branch
!
!
!
enable secret 5 $1$mERr$9cTjUIEqNGurQiFU.ZeCi1
!
!
!
!
!
!
!
!
!
!
!
ip ssh version 1
!
!
spanning-tree mode pvst
!
!
!
!
interface FastEthernet0/0
 no ip address
 duplex auto
 speed auto
!
interface FastEthernet0/0.40
 encapsulation dot1Q 40
 ip address 10.10.40.1 255.255.255.0
!
interface FastEthernet0/0.50
 encapsulation dot1Q 50
 ip address 10.10.50.1 255.255.255.0
!
interface FastEthernet0/0.55
 encapsulation dot1Q 55 native
 ip address 10.10.55.1 255.255.255.0
!
interface FastEthernet0/0.80
 encapsulation dot1Q 80
 ip address 10.10.80.1 255.255.255.0
!
interface FastEthernet0/1
 no ip address
 duplex auto
 speed auto
 shutdown
!
interface Vlan1
 no ip address
 shutdown
```

```
!  
ip classless  
!  
!  
!  
banner motd ^CAuthorized Access Only!^C  
!  
!  
!  
!  
line con 0  
  password cisco  
  login  
!  
line aux 0  
!  
line vty 0 4  
  password cisco  
  login  
line vty 5 15  
  password cisco  
  login  
!  
!  
!  
end
```

Branch#